## **PURITY C**

## Accessories and spare parts





BRITA FlowMeter 10 - 100	
Display unit (L/W/H)	62 / 62 / 22 mm
Sensor	80 / 50 / 26 mm
Flow range	10 - 100 l/h
Flow deviation	± max. 5%
Operating pressure	max. 8.6 bar
Pressure loss with flow of 1001/h	< 0,3 bar
Water intake temperature	4 - 30 °C
Cable length	max. 1.5 m
Inlet connection	G 3/8" Union nut
Outlet connection	G 3/8"
Order number	1033041

Calculates the residual capacity of the filter after the relevant filter capacity is set by recording the volumetric flow. Installed horizontally. With capacity indicator. FlowMeter is now equipped with a Velcro adhesive spot for comfortable fixation.



Service cartridge	
Dimensions (L/W/H)	125 x 125 x 233 mm
Max. filling volume cartridge cup	0.5 I
Operating pressure	0.5 - 8.6 bar
Water intake temperature	4 - 30 °C
Min. volume flow	2 l/m
Weight	350 g
Durability	2 years/max. 250 applications
Order number	1006579

Delivery without filter head.

The BRITA service cartridge is inserted temporarily in a PURITY C filter head in place of the filter cartridge in order to clean terminal devices. It is then filled with disinfected cleaning agents. The water which flows through the filter system flushes the cleaning agent directly into a connected terminal device. Fits in all PURITY C filter heads.



PURITY C wall mounting bracket	
Order number	1000480 (Pack 1)
Applicable for the sizes from CEO to CEOO	



Wall mounting bracket	
Dimensions (L/W/H)	212,2 x 271,5 x 453,5 mm
Order number	1015502 (Pack 1)
Applicable for the sizes CEOO C1100	)



PURITY C base	
Order number	1000494 (Pack 3)
Applicable for the sizes C50, C150, C	300.



Backflow preventer 3/8"	
Order number	1000639 (Pack 3)



Backflow preventer with securing clips JG8\*

Order number 292069 (Pack 1)



Reducer sets

Order number 1000898 (Pack 2)

3/4" external thread - 3/8" internal thread



Securing clips for JG\* connections

Order number 536801 (Pack 50)



Gasket set I

Order number 321800

- 3x flat gasket 3/4"
- 2x flat gasket 3/8"
- 2x O-rings (1" and 3/4" for inlet/outlet of filter head)

\*Not available for Switzerland.

For more information please contact:

BRITA Water Filter Systems Ltd.

BRITA House | 9 Granville Way | Bicester | 0X26 4JT | United Kingdom Tel.: +44 844 742-4990 | Fax: +44 186 936-5962

clientservices@brita.co.uk | www.brita.co.uk

BRITA Water Filter Systems Distributors Pty Ltd

Suite 2, Level 9, 123 Epping Road | Macquarie Park, NSW, 2113 | Australia Tel.: +61 1300 955-021 | NZ: 0800 482-008

professional@brita.com.au | www.brita.com.au

Headquaters: BRITA GmbH

Heinrich-Hertz-Strasse 4 | 65232 Taunusstein | Germany Tel.: +49 6128 746-0 | Fax: +49 6128 746-5033

info@brita.net | www.brita.de



## BRITA Professional Filter Service App

The Filter Service App is your ideal assistant. This unique, comprehensive tool helps determine the right type and size of filter for your precise needs. It provides detailed installation guidance for service engineers, calculates when cartridges will need replacing – and has a wealth of other, innovative capabilities.

Download for free on



